





















# TECHNICAL DATA

RANGE	E-VO CONCEPT+		E-VO CONCEPT	
	MACHINE TYPE	HOOD TYPE	UNDER COUNTER	UNDER COUNTER
MODEL	COP-174W (HRS)	COP-504W	CO-502W	CO-402W
Wash Cycles (seconds)	55-75-120	60-90-180	60-90-180	90-120-180
Continuous cycle	•	-	-	-
Max Productivity (*)				
Baskets/hour	60	40	30	30
Dishes/hour	1080	720	540	-
Glasses/hour	2160	1440	1080	1080
Standard Basket size (inches)	19 3/4 x 19 3/4	19 3/4 x 19 3/4	19 3/4 x 19 3/4	15 3/4 x 15 3/4
Able for 12 x 20 pans	•	•	•	-
Dimensions (inches)				
Width	26	23 5/8	23 5/8	18 1/2
Depth	30 1/8	23 5/8	23 5/8	20 1/2
Height	60 5/8	32 3/4	32 3/4	28 3/8
Useful Loading Height (clearance)	17 1/3	15 3/8	15 3/8	10 7/8
Open Hood Height	81 1/3	-	-	-
Capacity (gallons)				
Wash Tank	8.98	5.28	5.28	3.43
Boiler	2.37	1.85	1.85	1.05
Water consumption per cycle	0.63	0.63	0.63	0.53
Power (kW)				
Tank heating element	4.5	2.8	2.8	2
Boiler/Booster heating element	12	1.8 - 3.7 - 5.6	2.8	2.8
Wash pump(s)	2 x 0.6	0.6	0.6	0.26
Rinse pump	0.26	0.26	-	-
Total power	17.7	6.2	6.2	3.06
Working Temperature (°F)				
Washing	140	140	140	140
Rinsing	185	185	185	185
Multipower	•	•	-	-
Multitension (230 V-1N / 230 V-3 / 400 V-3N)	•	•	•	-
Water Protection Rating	IPx4	IPx4	IPx4	IPx4
Noise level (dBA)	<65	<65	<65	<70
Rinsing Aid Dispenser	•	•	•	•
Detergent Aid Dispenser	•	•	•	•
Drain Pump	O	•	•	•
Pressure Pump	•	•	-	-
Double Skin Door	-	•	•	•
Double Skin Body	-	•	•	-
Wash & Rinse Arms - AISI-304	•	•	•	•
Filter trays AISI-304 in the wash tank	•	•	•	-
Electronic control panel and thermal-stop	•	•	•	•

- Standard
  - O Option
  - Not version
- (\*) Assumed 18 dishes/rack 36 glasses/basket and 7 trays/rack  
Fagor reserves all rights to modify the data included in this catalogue.

**(800) 777-9129**