



NUTS
PGS. 6-9



STEMS
PGS. 6-9



WASHERS
PGS. 6-9



STRAIGHT SWIVELS
PGS. 6-9



FEMALE FLARE TO
BARB
PG. 7



SPLACERS
PG. 10



SPLACERS -
REDUCERS
PG. 11



SPLACERS - 90°
PG. 12



BARB HOSE TEES
PGS. 13-14



BARB HOSE CROSSES
PGS. 14-15



Y-TEES
PG. 16



Y-CROSSES
PG. 16



PLUGS
PG. 17



CAPS
PG. 17



MALE FLARE TEES
PG. 18



BARB TO
MALE FLARE
PG. 18



FEMALE FLARE TO
MALE FLARE TEES
PG. 19



FEMALE FLARE TO
MALE FLARE TEES
PG. 19



BARB TEES TO
FEMALE FLARE
PG. 19



BARB CROSSES TO
FEMALE FLARE
PG. 19



FEMALE FLARE TO
BARB TEES
PG. 20



FEMALE FLARE TO
BARB ELBOWS
PG. 20



FEMALE FLARE TO
MALE FLARE ELBOWS
PG. 20



BARB TEES
TO NPT
PG. 21



MALE FLARE TEES
TO NPT
PG. 21



BARB TEES TO
FEMALE NPT
PG. 21



BARB TO
MALE FLARE
PG. 22



MALE FLARE TO
MALE FLARE
PG. 22



BULKHEAD ADAPTERS
PG. 22



NPT TO
MALE FLARE
PG. 23



NPT TO MALE
FLARE ELBOWS
PG. 23



FEMALE FLARE
TO MALE FLARE
PG. 23



BARB TO NPT
PG. 24



BARB TO
NPT ELBOWS
PG. 24



BARB TO NPT
ELBOWS SWEEP
PG. 25



NPT TO NPT
ELBOW
PG. 25



BARB TO
FEMALE NPT
PG. 26



SWIVELS
ELBOWS
PG. 27



SWIVELS - 45°
PG. 27



U-BENDS
PG. 28



U-BEND MANIFOLDS
SINGLE MALE FLARE
PG. 28



U-BEND MANIFOLDS
SINGLE BARB
PG. 29



U-BEND MANIFOLDS
MULTI BARBED
PG. 30



U-BEND MANIFOLDS
MALE FLARE
PG. 30



MANIFOLDS - STRAIGHT
MALE FLARE AND BARBED
PG. 31



WUNDER-BAR
INLETS - STRAIGHT
PG. 32



WUNDER-BAR
INLETS - 45° AND 90°
PG. 32



SHURFLO INLETS
STRAIGHT
PG. 33



SHURFLO INLETS
- 90°
PG. 33



FLOJET INLETS
STRAIGHT AND 90°
PG. 34



FLOJET INLET - U-BEND
MANIFOLDS
PG. 34



FLOJET INLET
STRAIGHT - QUAD PORT
PG. 34



VALVE INLETS -
STRAIGHT
PG. 35



VALVE INLETS -
45° AND 90°
PG. 35



BEER NUTS
PG. 36



BEER CAP NUT
PG. 36



BEER STEMS
PG. 36



BEER STEM -
ELBOWS
PG. 37



BEER WING
NUT
PG. 37



BEER WASHER
PG. 37



BEER STEM -
MALE FLARE
PG. 37



BEER GAS
NIPPLE
PG. 37



STAINLESS WALL
BRACKET - BEER
THREAD TO BARB
PG. 38



STAINLESS WALL
BRACKET - STRAIGHT
SPLICER
PG. 38



STAINLESS WALL
BRACKET - 45°
SPLICER
PG. 39



STAINLESS WALL
BRACKET - U-BEND
PG. 39



STAINLESS WALL
BRACKET - BEER
THREAD TO BARB
PG. 39



STAINLESS WALL
BRACKET - BEER
THREAD
PG. 39



JUG GROWLER
FILLER
PG. 40



BARB ELBOW TO
SMOOTH FINISH - 90°
PG. 40



BARB ELBOW TO
SMOOTH FINISH - 45°
PG. 40



FAUCET LEVER
PG. 40



QUICK DISCONNECT
TO BEER
THREAD - U-BEND
PG. 41



STAINLESS WALL BRACKET
BARB TO BEER - THREAD
U-BEND MANIFOLD
PG. 41



STAINLESS 6-WAY
BEER CLEANING
MANIFOLD - STAR
PG. 41



STAINLESS BEER
MANIFOLDS
PG. 42-44



STAINLESS 6-WAY
BEER MANIFOLD
PG. 44



BARB TO SMOOTH
FINISH
PG. 44



TUBE
COMPRESSION
TO BARB
PG. 45



TUBE COMPRESSION
TO MALE FLARE
PG. 45



FEMALE FLARE TO
BARB COMPRESSION
PG. 45



FEMALE FLARE
TO MALE FLARE
COMPRESSION
PG. 46



QUICK
DISCONNECT
ADAPTERS
PG. 46



QUICK DISCONNECT
ADAPTERS - ELBOW
PG. 46



QUICK
DISCONNECT
ADAPTERS - NPT
PG. 46



STARTER
KIT
PG. 47



OETIKER STEPLESS
EAR CLAMPS
PG. 48



OETIKER PINCERS
PG. 49



TUBE CUTTER
PG. 49



CO₂ WRENCH
PG. 49



BARBED SHUT-OFF
VALVE
PG. 49



LOOSE
COLD PLATES
PG. 50



SEALED IN
COLD PLATES
PG. 51



CHILLER PLATES
PG. 52



CHECK VALVE - NPT
TO MALE FLARE
PG. 52



CHECK VALVE -
SINGLE BALL -
NPT TO MALE FLARE
PG. 53



CHECK VALVE -
DOUBLE BALL - NPT
TO MALE FLARE
PG. 53



CHECK VALVE
- DOUBLE BALL
- BARBED
PG. 53



STAINLESS SHUT-OFF
VALVE - MALE FLARE TO
FEMALE FLARE - ELBOW
www.HaftPricé.com



PRESSURE RELIEF
VALVE - NPT
PG. 54



STAINLESS SHUT -
OFF VALVE - MALE
FLARE TO MALE FLARE
PG. 54



N₂ INLET -
NIPPLE
PG. 55
(800) 777-9129




CO₂ CHANGE-
OVER VALVE
MALE FLARE 3-WAY
PG. 55

INDEX

PRODUCTS	Nuts, Stems, Washers and Straight Swivels	6
	Splicers	10
	Barbed Tees and Crosses	13
	Caps and Plugs	17
	Male and Female Flare Adapters	18, 22
	NPT Adapters	21, 23
	Swivels	27
	U-Bends and Manifolds	28
	Valves and Pumps	32
	Beer	36
	Compression	45
	Quick Disconnect Adapters	46
	Starter Kit	47
	Oetiker Clamps	48
	Cold Plates	50
	Check Valves, Pressure Relief Valves and Shut-Off Valves	52

HOW TO USE THIS CATALOG

FITTING TABLES	The subsequent pages of this catalog contain diagrams and tables with data for each family of fittings. Each diagram has several letters on it that correspond to the relevant table's column headers wherein you will find the measurements for a particular part number.
BARBS	All barbs are listed in inches and millimeters. The inch measurement represents the ID of the tubing for which the barb is designed to work. The millimeter measurement is the actual outside diameter of the barb.
THREADED FITTINGS	All threaded fittings are listed in the Unified Thread Standard format, e.g. 7/16" 20 UNF.
LENGTH/HEIGHT	All length and height data are actual measurements of the fittings in both inches and millimeters.
PART NUMBER COLOR CODING	 - These fittings are part of our "economy line". For most, the part number listed directly above it in the fittings table will be identical US-manufactured version of the economy fitting and will have a similar part number, e.g. 7006 and 9006.
O-RINGS	All parts designed for o-rings will be shipped with o-rings installed unless otherwise requested by the customer.

CONVERSION TABLE

Nominal Inch	Actual Barb OD (")	Actual Barb OD (mm)	Matching Thread	Nominal Millimeter
1/8"	0.160"	4.06 mm		4 mm
5/32"	0.180"	4.57 mm		4.4 mm
3/16"	0.250"	6.35 mm		6 mm
1/4"	0.281"	7.14 mm	7/16" 20 UNF	6.5 mm / 7 mm
5/16"	0.340"	8.64 mm	1/2" 16 UNF	8 mm
3/8"	0.390"	9.96 mm	5/8" 18 UNF	9 mm / 9.5 mm / 10 mm
7/16"	0.450"	11.43 mm		11 mm
1/2"	0.531"	13.49 mm	3/4" 16 UNF	13.5 mm
3/4"	0.782"	19.86 mm		20 mm

NOMINAL INCH	Barb size designated to match the ID of beverage tubing.
ACTUAL BARB OD (")	The actual outside diameter of the barbed fitting in decimal format in inches.
ACTUAL BARB OD (MM)	The actual outside diameter of the barbed fitting in millimeters.
MATCHING THREAD	The unified thread standard that is normally used with a nominal inch fitting, e.g. a 1/4" nut has a 7/16" 20 UNF thread count.
NOMINAL MILLIMETER	Best practice conversion of inch based fittings onto metric based beverage tubing, e.g. 1/2" barb fitting can be used on 13.5 mm OD beverage tubing.